



## BS MULTI 450 / \*750 Servo punch machine



The most universal and most sold model by far for the mid capacity range to 10,500 cycles/h.



- Simple operation from touchscreen
- Integrated controller for infeed hole punching

Available in two working widths.

## Technical details

<b>Capacity</b>	max. 10'500 cycles/h (depending on format and quality)
<b>Drive</b>	servo motor, 3,5 kW
<b>Feed</b>	adjustable belt transfer with lower and upper belts
<b>Feed length</b>	900 or 450 mm
<b>Feed swivel area</b>	900 mm length = 540 - 940 mm 450 mm length = 760 - 940 mm
<b>Exit height</b>	940 mm
<b>Working width</b>	max. 450 mm / *680 mm
<b>Format</b>	see separate data sheet format
<b>Max. product thickness</b>	perforation up to 2 mm, filing-hole punching up to 5 mm, cutting up to 5 mm, die-cutting up to 2 mm (depending on format and quality)
<b>Product alignment</b>	stop- and side adjustment elements
<b>Timing control</b>	pulse-independent by photo cell
<b>Tool attachment</b>	attachment for filing-hole and cutting tools, profile insert for perforating-tools, attachment for die-cutting-tools
<b>Compressed air</b>	6 bar (provided on site)
<b>Transportable with</b>	pallet truck
<b>Space requirement</b>	approx. 1'800 or 1'350 mm x 1'100 mm / *1'200 mm (L x B)
<b>Weight</b>	approx. 800 kg / *1'350 kg
<b>Power supply</b>	3 x 400VAC / N / PE / 50/60Hz / 32A

## Accessory



- Cutting equipment
- Die-cutting equipment
- Front cut equipment in infeed
- Hole punching systems
- WIRE-O and corner perforation tools