



## SAB 550 / \*750 stream delivery



The SAB 550 / 750 stream delivery is used for multiple-up production. Formats from A3 to 35 x 35 mm (minimum) can therefore be delivered in streams

- Round belt infeed for optimised product delivery
- Powered top belts with size-independent stream belt
- Preselection and total counters
- Motorised height adjustment

Available in two working widths, optionally with stream belt extension to 2 meters



## Technical details

<b>Working width</b>	max. 550 mm / *750 mm
<b>Height adjustment</b>	motor driven, 690 - 950 mm
<b>Feed</b>	with round belts
<b>Speed</b>	20 - 200 m/min, adjustable
<b>Stream belt</b>	40 mm retractable to infeed
<b>Stream belt length</b>	1'050 mm / optional 2'000 mm
<b>Upper belts</b>	8 units, 35 mm, driven
<b>Overlap</b>	10 - 100 mm
<b>Counter</b>	preselection and sum counter, scale of 0 - 40 mm or jump feed, adjustable, performance indicator
<b>Space requirement</b>	approx. 2'050 x 800 mm / *1'050 mm (L x B)
<b>Weight</b>	approx. 300 kg / *350kg
<b>Power supply</b>	3 x 400VAC / N / PE 50/60Hz / 16A
<b>Power</b>	2 x 0,37 kW
<b>Lift motor</b>	0,25 kW