BS MULTI 450 / *750 Servo punch machine

The most universal and most sold model by far for the mid capacity range to 10,500 cycles/h.

Bograma AG - Mettlenstrasse 1 - CH-8488 Turbenthal - Telefon +41 (0)52 396 27 70

- Simple operation from touchscreen
- Integrated controller for infeed hole punching

Available in two working widths.

Technical details

Capacity	max. 10'500 cycles/h (depending on format and quality)
Drive	servo motor, 3,5 kW
Feed	adjustable belt transfer with lower and upper belts
Feed length	900 or 450 mm
Feed swivel area	900 mm length = 540 - 940 mm 450 mm length = 760 - 940 mm
Exit hight	940 mm
Working width	max. 450 mm / *680 mm
Format	see separate data sheet format
Max. product thickness	perforation up to 2 mm, filing-hole punching up to 5 mm, cutting up to 5 mm, die-cutting up to 2 mm (depending on format and quality)
Product alignment	stop- and side adjustment elements
Timing control	pulse-independent by photo cell
Tool attachment	attachment for filing-hole and cutting tools, profile insert for perforating-tools, attachment for die-cutting-tools
Compressed air	6 bar (provided on site)
Transportable with	pallet truck
Space requirement	approx. 1'800 or 1'350 mm x 1'100 mm / *1'200 mm (L x B)
Weight	approx. 800 kg / *1'350 kg
Power supply	3 x 400VAC / N / PE / 50/60Hz / 32A

Accessory



- Cutting equipment
- Die-cutting equipment
- Front cut equipment in infeed
- Hole punching systems
- WIRE-O and corner perforation tools

Bograma AG - Mettlenstrasse 1 - CH-8488 Turbenthal - Telefon +41 (0)52 396 27 70